AS: One automatic slack adjuster type of CNF.

The AS Automatic Slack Adjuster combines easy installation and outstanding performance in a double sealed package for longer brake lining life with consistent, safer brake performance.



- 5″, 5-1/2″, 6″, 6-1/2″ Arm Lengths
- Straight or Offset clevis with 1/2″ or 5/8″ threads
- Unhanded design
- Compact housing for easy installation
- Double sealed actuator arm
- Drilled worm wheel
- Factory lubricated and sealed
- Extended life clevis pin bushing
- O-Ring on spline gear
- Available in 10, 24, 28, or 37 spline configurations

| Part number | Ref number | Casting number | CLEVIS THREAD | Spline teeth | L |
|---|---|---|---|---|---|
| CN801132 | AS1132 | 100401 | 1/2"-20 & 5/8"-18 | 10-SAE1-1/2" | 5-1/2" |
| CN801133 | AS1133 | 100401 | 5/8"-18 | 10-SAE1-1/2" | 6" |
| CN801136 | AS1136 | 100401 | 1/2"-20 & 5/8"-18 | 10-SAE1-1/4" | 5-1/2" |
| CN801138 | AS1138 | 100401 | 1/2"-20 & 5/8"-18 | 24-SAE1-1/4" | 5-1/2" |
| CN801140 | AS1140 | 100401 | 1/2"-20 & 5/8"-18 | 28-SAE1-1/2" | 5-1/2" |
| CN801141 | AS1141 | 100401 | 5/8"-18 | 28-SAE1-1/2" | 6" |
| CN801144 | AS1144 | 100401 | 5/8"-18 | 37-SAE1-5/8" | 6" |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |